



# UTTO TRACTOR BM

Hydraulic and Transmission Oil

## Description

Utto Tractor BM is a special oil, intended for automatic transmissions, hydraulic systems, wet brakes, converters for tractors, forklifts and different off-highway equipment.

This oil has the following advantages:

- Low pour point, no problem to start until -20°C.
- Excellent protection against wear and corrosion.
- High resistance against foaming.
- Contains anti-corrosion additives.
- High viscosity index.

## Quality level

API:	GL 4
CASE IH:	MS 1206, 1207, 1209, 1210
ALLISON:	C4
JOHN DEERE:	J20 C
CASE NEW HOLLAND:	MAT 3505, 3525, 3526
VOLVO CONSTRUCTION EQUIPMENT:	WB-101
MASSEY FERGUSON CMS:	M1135, M1143, M1145
FORD NEW HOLLAND:	M2C-134D/FHNA 2C 201.00
ZF:	TE-ML 03E, 05F, 06K, 17E

## Available in

Carton of 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

- Transmissions, lifters, drives, wet brakes of agricultural tractors and off highway equipment.
- Mobile hydraulic systems (cranes, PTO-converters, power steering).
- Drives and hypoid tractor converters (except for those which need a GL 5 oil).

## Photo



## Typical properties

Density 15°C	0.876
Viscosity cst 40°C	62.6
Viscosity cst 100°C	10.7
Viscosity index	162
Pourpoint °C	-39
Flashpoint COC °C	212

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)