



# UNIVERSAL TRACTOR OIL SAE 10W30 – 15W30

Universal oil for tractors

## Description

Universal Tractor Oil is a universal multi-grade oil for engines, transmissions, wet brakes and hydraulic systems of tractors.

- Good protection against corrosion
- Good detergency and dispersancy
- Strong protection against wear
- One oil for lubrication of all parts

## Quality level

API:	CG-4, SF-CE, GL-4, GL-5 (Low speed-high torque)
ACEA:	E3
JOHN DEERE:	JDM J27
FORD:	ESN-M2C-159B/C, 134C/D, FNH-82009201
ZF:	TE-ML 03A/05K/06B/07B/07D
MASSEY FERGUSON:	M1135/M1139/M1143M1144/M1145
NEW HOLLAND:	030C/410C/420A
AFNOR:	NFE68-603E
ALLISON:	C4 (Agricult. applic.)
MAN:	271
MB:	227.1
CASE:	MAT 3525/3526

## Available in

Cartons of 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

This multi-grade oil is advised for the lubrication of either charged or not charged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-highway equipment.

## Photo



## Typical properties

	SAE 10W30	SAE 15W30
Density 15°C	0,869	0,874
Viscosity cst 40°C	75	81,7
Viscosity cst 100°C	11,4	10,8
Viscosity index	144	118
Pourpoint °C	-35	-34
Flashpoint COC °C	216	220

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)



**DENICOL**  
LUBRICANTS

DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> ● EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)