



# ALCAT TDTO SAE 10W, 30, 50

Transmission Drive Train Oil

## Description

Alcat TDTO is extremely suitable to meet the requirements of Caterpillar and is highly recommended for their Power Shift transmissions, wet brakes and final drives, differentials and bevel gears. This lubricant also meets the standards of Cat TO-2 and Allison C4, it has the following characteristics:

- Excellent anti wear protection
- Outstanding anti oxidation protection
- Good fluidity at low temperature

## Quality level

ALLISON	C4
CATERPILLAR	TO-4
ISO	100
KOMATSU	KES 07.868.1

## Available in

Barrels of 30, 60 and 208 L.

## Application

Alcat TDTO is extremely suitable to meet the requirements of Caterpillar and is highly recommended for their Power Shift transmissions, wet brakes and final drives, differentials and bevel gears.

## Photo



## Typical properties

	SAE 10W	SAE 30	SAE 50
Density 15°C	0.864	0.894	0.904
Viscosity cst 40°C	38.7	108	217
Viscosity cst 100°C	6.61	11.4	18.8
Viscosity index	125	91	91
Pourpoint °C	-33	-31	-27
Flashpoint COC °C	248	185	238

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)