



# COMPETITION INJECTION 2 STROKE OIL

Synthetic 2-stroke Oil specially formulated for Injections Systems

## Description

Racing 2 Syntex is a hi-tech 2-stroke injector lubricant for pre-mix and injection systems. Contains synthetic base oils and is an extremely thin substance. Provides optimum performances and keeps the engine clean. Prevents carbon deposition and other degradations. For high power engines.

## Quality level

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

For high-speed 2-stroke engines.

## Photo



## Typical properties

Density 15°C	0.877
Viscosity cst 40°C	79.3
Viscosity cst 100°C	11.4
Viscosity index	135
B.N.(HClO4-methode)	1.1
Pourpoint °C	190°C-240°C
Flashpoint COC °C	61

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> ● EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)