



---

# GEAR OIL HYPOID EP GL.5 SAE 85W140

Extreme Pressure High Performance Transmission & Gear Oil

---

## Description

Gear Oil Hypoid EP GL.5 SAE 85W140 is a lubricant, extremely suitable for use in heavy duty transmissions in rear axles, gear boxes and all transmissions where an API GL.5 oil is recommended. This oil is also extremely suitable for worm wheels, spiral bevel gears and most transaxles. This oil guarantees excellent friction properties, resulting in very smooth gear shifting without vibrations.

- Very high oxidation and thermic stability
- Safe for seals
- Longer maintenance intervals
- Excellent anti-wear protection

## Quality level

API: GL-5  
ZF: TE-ML 05A, 07A, 12E, 16B, 16C, 16D, 17B, 19B,  
MIL: MIL-L-2105 C/D

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Suitable for use in heavy duty transmissions in rear axles, gear boxes and all transmissions where an API GL.5 oil is recommended.

## Photo



## Typical properties

Density 15°C	0.908
Viscosity cst 40°C	367
Viscosity cst 100°C	26.1
Viscosity index	95
Pourpoint °C	-17
Flashpoint COC °C	215

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)