



MULTI MOLY GREASE EP 2

Lithium Molybdeen Extreme Pressure High Impact Parts Grease

Description

Multi Moly Grease EP 2 is a high qualified grease, with molybdeendisulfide, other additives, and lithium as a thickener, to obtain the following properties:

- Strong adhesion to metal.
- An excellent water-resistance
- A very good stability.
- A good activity against wear and corrosion.
- A low friction coefficient
- A good resistance against high pressure.

Quality level

NLGI 2

Available in

Carton of 24x400 Gr (Tubes)
Bottles of 1 and 5 Kg.
Barrels of 18, 50 and 180 Kg.

Application

This grease may be used for the lubrication of heavily loaded pivots and turntables of carriers working under shockload-conditions and sudden overloading.
This grease is also advised for the lubrication of lubrication points that are attainable with difficulty.

Photo



Typical properties

Thickener	Lithium
Dropping point	190
Base oil viscosity cst 40°C	110
Base oil viscosity cst 100°C	12
4-Ball weld load	3200 N
Temperature range	-30°→120° C
Colour	Dark Grey

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com