



MULTI SYN ATF FE

Full Synthetic Automatic Transmission Fluid

Description

Multi Syn Atf Fe is a full synthetic transmission fluid for automatic transmissions with a very high viscosity index. It guarantees a longer service life of the transmission.

It has following characteristics:

- Excellent oxidation stability
- Very good friction and anti-wear properties
- Fuel economy

It is conform to the requirements of European, Japanese and American manufacturers.

Quality level

FORD	MERCON SP, MERCON LV, WSS-M2C924-A
MB	236.12
VW	G 055 162, 055 005, 055 540, 060 162
BMW	M-1375.4, 83222152426
AISIN WARNER	JWS 3324, AW-1
MITSUBISHI	ATF J3
TOYOTA	AUTO FLUID WS
MAZDA	FZ
HYUNDAI	NWS-9638 T5, SP-IV, SPH-IV
HONDA	DW-1
NISSAN	MATIC-S
CHRYSLER	68157995AA
FIAT	9.55550-AV2, 9.55550-AV5
JAGUAR	02JDE26444
LAND ROVER	LR023288

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

This transmission fluid can be used in the latest generations of most automatic transmissions and torque converters of off-road vehicles, SUVs and passenger cars.

Photo



Typical properties

Density 15°C	0.849
Viscosity cst 40°C	29.4
Viscosity cst 100°C	6.1
Viscosity index	162
Pourpoint °C	-46
Flashpoint COC °C	211
Colour	Red

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> • EMAIL denicol@denicol.com