



## MULTI SYN ATF

Full Synthetic Transmission Fluid

### Description

Multi Syn ATF is a full synthetic fluid for automatic transmissions and torque converters of cars, SUV's and off-road vehicles.

It has following features:

- Very high viscosity index
- Excellent thermal and oxidation stability
- Very good friction and anti-wear properties
- Reduces sludge and formation of deposits
- Very good performance at low temperatures
- Improved cold start
- Excellent pumpability

### Quality level

FORD	MERCON V
MB	236.11, 236.3, 236.7, 236.10
ALLISON	TES 295
VW	G 052 025, 052 055, 052 162, 052 533, 052 990, 055 025
BMW	LA 2634, LT 71141, ETL 7045E, ETL 8072B
GM	DEXRON III-H
CHRYSLER	ATF +3 AND +4
TOYOTA	TYPE T-IV
HYUNDAI	SP-III
HONDA	ATF Z-1
NISSAN	MATIC J, K, W
AISIN-WARNER	JWS 3309, 3314, 3317

### Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

### Application

Suitable for automatic transmissions and torque converters of cars, SUV's and off-road vehicles.

### Photo



### Typical properties

Density 15°C	0.850
Viscosity cst 40°C	30.3
Viscosity cst 100°C	6.3
Viscosity index	165
Pourpoint °C	-47
Flashpoint COC °C	217
Colour	Red

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)