



SUPERIOR SYNFLEET L.S. SAE 10W40

Synthetic Blend Engine Oil – High Tech “Low SAPS” Emission Oil

Description

Superior Synfleet L.S. is a new generation, 'Low SAPS', extra high performance lubricant, formulated from specially selected, high-quality base oils and a customized additive package.

It supports the exceptional performance of modern heavy-duty engines and offers complete protection of the DPF.

This oil offers the following advantages:

- Full after-treatment system protection.
- Lower maintenance cost
- Total engine protection: outstanding engine cleanliness and durability.
- Long oil drain intervals.
- Life time of particulate filters

Quality level

API	CJ-4, CI-4
ACEA	E7-04 Issue 2, E9-08 Issue 2
CATERPILLAR	ECF-3
CUMMINS	CES 20081
MB	228.31, 228.51
MAN	M 3477,3575
MTU	Type 3.1
VOLVO	VDS-4
RENAULT TRUCKS	RLD-3
MACK	EO-O
GLOBAL	DHD-1
JASO	DH-1, 2

Available in

Barrels of 30, 60 and 208 L.

Application

Superior Synfleet L.S. is recommended for the latest 4-stroke diesel engines fitted with DPF, which have to answer to the strict limitations of exhaust gases.

Equally suitable for older diesel engines with EGR (Euro III, IV and V + Tier I, II, III and IV).

Exceeds the demanding requirements of most U.S., European and Japanese manufacturers.

Photo



Typical properties

Density 15°C	0.863
Viscosity cst 40°C	91.2
Viscosity cst 100°C	13.9
Viscosity index	152
Pourpoint °C	-35
Flashpoint COC °C	226
Sulphated Ash	1.0

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)

TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.

URL <http://www.denicol.com> • EMAIL denicol@denicol.com