



# ULTRA SYNTRUCK FE 5W30

Full Synthetic Ultra High Performance Diesel Oil

## Description

Ultra Syntruck FE 5W30 is a full synthetic, ultra high performance lubricant, specially developed to meet the highest performance standards for large trucks. This 'Low SAPS' oil, compatible with EURO 5 standards, can be used in engines with particulate filters and in combination with low-sulfur diesel (maximum 50 ppm). It is also suitable for most of the Euro VI-engines. This oil offers a full protection of the after-treatment system, an excellent cleanliness and durability of the engine and an outstanding CO2 reduction and fuel economy.

## Quality level

MB	228.51, 228.31, 235.28
MAN	M3477, M3677, M3271-1
ACEA	E6-08 Issue 2, E7-08 Issue 2, E9-08 Issue 2
MACK	EOM PLUS, EO-N Premium Plus, EO-O Premium Plus
API	CJ-4, SN
MTU	Type 3.1-2.1
RENAULT	RLD-2, RLD-3, RXD, RGD
DEUTZ	DQC IV-10 LA
VOLVO	VDS-3, VDS-4, CNG
JASO	DH-2
CATERPILLAR	ECF-3
SCANIA	LA

## Available in

Barrels of 30, 60 and 208 L.

## Application

Suitable for large truck engines answering to the EURO 5-standard and most of the Euro 6 engines as well as the latest generation of agricultural machinery.

## Photo



## Typical properties

	SAE 5W30
Density 15°C	0.856
Viscosity cst 40°C	70.9
Viscosity cst 100°C	11.9
Viscosity index	165
Pourpoint °C	-45
Flashpoint COC °C	232

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)