



TURBO SELECT

High Performance – Multigrade Engine Oil

Description

Turbo Select is a universal engine oil, suitable for all 4-stroke gasoline and diesel engines. The product has a very high resistance against oxidation, high detergent and dispersant properties, a high neutralizing power, strong resistance, high lubrication power, a very large application field and a low loss by evaporation.

Quality level

API	SJ/CF-4 (D-CE), CF
ACEA	A2-96 Issue 2, B3-98, E2-96 Issue 2
VW	501.01/505.00 (11-92)
CAT	TO-2
MACK	EO-K/2
MERCEDES	228.1, 229.1
MAN	271
ALLISON	C-4
VOLVO	VDS

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Intended for the transport sector and civil engineering and may be used during the whole year. This oil is especially recommended for mixed fleets (passenger cars and vehicles).

It can be used in all services during the whole year, in diesel engines, with natural aspiration or turbo charged and in all gasoline engines, according to the severe service prescriptions.

Photo



Typical properties

	SAE 15W40
Density 15°C	0.883
Viscosity cst 40°C	107
Viscosity cst 100°C	14.0
Viscosity index	132
Pourpoint °C	-30
Flashpoint COC °C	228
Sulphated Ash	1.3

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com